

CASE II
AGRICULTURE

COMPACT FARMALL® C CVT

SERIES TRACTORS



THE FARMALL C CVT – DRIVES LIKE A CAR.

The continuously variable transmission (CVT) is designed to provide smooth, seamless speed changes through varying conditions. The transmission controls are simple, which allows you to be more productive and is especially helpful for the less-experienced operator. Just select forward or reverse, push the single pedal, and go – the transmission automatically adjusts to deliver the desired speed and match load conditions. It's even got cruise control. What's more, the CVT gets the job done quietly and efficiently, so whatever you're doing feels less like work and more like fun.



FARMALL C CVT COMES WITH A GENEROUS LIST OF STANDARD EQUIPMENT AND FEATURES, INCLUDING*:



*Ask your dealer about other options and available features.

DELUXE ACCOMMODATIONS PLUS EASY OPERATION.

Farmall C CVT tractors offer deluxe features with ease of operation, superior visibility and the fastest road speed of any compact tractor. Compatible with a long list of available attachments and complimentary implements, these tractors tackle diverse and demanding jobs from livestock operations to landscaping and municipality maintenance needs.



ULTIMATE OPERATOR ENVIRONMENT.

The Farmall C CVT models have one of the roomiest compact-tractor cabs available, with:

- Easy entrance and exit on both sides
- Opening rear window for fresh air circulation
- A supportive, adjustable, cloth seat
- Optional factory-installed radio
- Connections and clips for your electronics
- A comfort-creating HVAC system
- Non-cab models are also available

DELUXE FEATURES THAT WORK HARD.

The Farmall C CVT is one of the fastest compact tractors on the market, with a top speed up to 19 mph. Two models featuring 45 and 53 engine horsepower are designed to get the work done efficiently and still save on fuel. Larger 13-gallon fuel tanks prevent the need for frequent fill-ups. A 3-point hitch lift capacity of 2,800 lbs. is ready to handle the implements of your choice, and the fully independent PTO system with electro-hydraulic PTO engagement saves you effort and time. Bottom line, these productivity-enhancing features help you get more done while enjoying the easy operation of the CVT transmission.

PRESS THE SWITCHES AND GO.

Easy-to-understand toggle switches on the control pod guide the CVT transmission, which allows you to decide how your tractor operates.

- A Reactivity toggle switch:** choose how quickly or slowly your tractor responds to operator input.
- B Speed toggle switch:** choose high for 100% max speed or low for 50% max speed.
- C 2WD/4WD toggle switch:** determines traction selection. Electronically controlled and can be engaged on the go.
- D Cruise control toggle switches:** just like a cruise control on a car, use the left toggle switch to turn the cruise on or off and the toggle switch on the right to set or resume. *(Note: the throttle should be turned up to 2,000 rpm to use this function.)*

A FULL LINE OF LOADERS, ATTACHMENTS AND IMPLEMENTS.

Choose from more than a dozen optional attachments that are quick and easy to switch out.



Specifications	L350A Loader
Lift Capacity at Bucket Pivot Pin	2,000 lbs. (907 kg)
Lift Capacity 19.7 in. (500 mm) from Bucket	1,540 lbs. (699 kg)
Max Lift Height	105 in. (2667 mm)
Dump Angle at Full Height	58 degrees
Rollback Angle at Ground	30 degrees
Bucket	72 in. HD material bucket

CASE IH LOADERS ARE READY TO WORK FOR YOU.

A loader turns a tractor into a versatile, powerful workhorse. All compact Farmall C CVT tractors come completely loader ready. The mounting brackets, joystick and controls, hydraulic valve and hoses and grill guard are already installed on the tractor. Just drive the tractor into the loader, put in the pins, attach the hydraulics and start working! Curved-boom loader arms let you easily see to the top of the bucket and around the front tires.

QUICK AND EASY ATTACHMENTS AND IMPLEMENTS.

With a heavy-duty 3-point hitch, high-capacity responsive hydraulics and independent PTO, your Farmall C CVT series tractor is ready for action.

- Side-discharge mower
- Rear-discharge mower
- Rear-mount finishing mower
- Front-mount rotary broom
- Rotary tiller
- Front-mount blade
- Front- and rear-mount snowblower
- Backhoe
- Rotary cutter
- Box blade
- Landscape rake
- Disk harrow
- Rear, 3-point mounted blade



COMPACT FARMALL® C CVT SERIES SPECIFICATIONS

MODEL	FARMALL 45C CVT	FARMALL 55C CVT
ENGINE		
Type	3-cylinder FPT, diesel, turbocharged & aftercooled	
Displacement	2.2 L (135.9 cu. in.)	
Gross engine HP	45.1 @ 2600 rpm	53 @ 2600 rpm
PTO HP	34	41
Emissions	Tier 4 B/Final	
Exhaust Treatment	Internal exhaust gas recirculation (EGR) plus Particulate Matter Catalyst	
Fuel System	Electronic, high pressure, common rail	
Fuel Capacity	13 gal. (49.2 L)	
TRANSMISSION		
Standard	Continuously Variable Transmission (CVT) - Chain Variator Drive	
3-POINT HITCH		
Lift Capacity @ 24 in. Behind Pins	2,800 lbs. (1 270 kg). Telescopic lower links and stabilizers	
PTO		
PTO Speeds	540 rpm for rear-mounted implements; 2,000 rpm mid-mount for mid- & front-mounted attachments	
HYDRAULICS		
System Type	Open center	
Pump Type	Engine driven dual gear-type	
Base Mid-Mount Remotes	2	
Base Rear Remotes	0	
Optional Rear Remotes	1 or 2	
Main Pump Flow	9.7 gpm (36.9 L/min.)	
Steering Pump Flow	5.4 gpm (20.4 L/min.)	
DIMENSIONS (17.5×24 R4 REAR TIRES)		
Overall Length	122 in. (3 098 mm)	
Overall Width	58.5 in. (1 485 mm)	
Overall Height (Cab / Non-cab)	92.7 in. (2 365 mm) / 97.4 in. (2 473 mm)	
Wheelbase	73.5 in. (1 867 mm)	
Turning Radius	116 in. (2 950 mm)	
Turnaround Diameter	142 in. (3 603 mm)	
WEIGHT		
Average Weight (Cab / Non-cab)	4,940 lbs. (2 240 kg) / 4,190 lbs. (1 900 kg)	

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2016 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com



CIH02021601